In the claims:

All claims standing for examination are presented below with appropriate status indication

- 1-37. (Cancelled)
- 38. (Currently amended) A method for transferring a packets of data from a source in a private network through the Internet back to a destination in the same private network across connected networks, comprising the steps of:
- (a) at a first node in a virtual private network (VPN), using a first header portion of a data packet, the first header portion indicating the first node as a source node and a second node in the VPN as a destination node, generating a value associated with the source and destination nodes:
- (b) creating a second <u>Internet protocol</u> (<u>IP</u>) header portion for the data packet <u>on a second network</u> including the value associated with the source and destination nodes;
- (c) using the second header portion, selecting one of a plurality of possible paths on a second network connected to the VPN for forwarding the packet <u>back to a</u> destination in the same VPN.
- 39. (Previously presented) The method of claim 38 wherein the second network is the Internet network
- 40. (Currently amended) The method of claim 38 wherein the first header portion is one or the other of an Ethernet header portion or an Internet Protocol (IP) header portion, and the second header portion is one or the other of an Ethernet header portion or an Internet Protocol (IP) header portion.
- 41. (Previously presented) The method of claim 38 wherein the value is derived by

performing a hash operation on the first header portion.

- 42. (Previously presented) The method of claim 41 wherein the hash operation is performed on information in the first header portion related to addresses of the source and destination nodes.
- 43. (Previously presented) The method of claim 41 wherein the hash operation is performed on a protocol field in the first header portion.
- 44. (Canceled)
- 45. (Previously presented) The method of claim 41 wherein the hash operation comprises performing a division on the first header portion.
- 46. (Previously presented) The method of claim 45 wherein the value is related to a remainder generated by the division.
- 47. (Previously presented) The method of claim 41 wherein the hash operation comprises a cyclic redundancy check.
- 48. (Previously presented) The method of claim 41 wherein the hash operation comprises a checksum operation.
- 49. (Previously presented) The method of claim 38 wherein the selecting step comprises performing a hash operation on the second header portion.
- 50. (Currently amended) A system for transferring a packet of data from a source in a private network through the Internet back to a destination in the same private network across connected networks, comprising:

a first and a second node in a virtual private network (VPN), each node coupled to a second Internet Protocol (IP) network; and

a data packet;

wherein the first node generates, using a first header portion of the data packet, a value associated with the first node as a source node and the second node as a destination node, creates a second <u>IP</u> header portion for the data packet including the value generated from the first header portion, and using the second <u>IP</u> header portion selects one of a plurality of possible paths through the second <u>IP</u> network for routing the data packet <u>from</u> the source in the VPN through the Internet back to a destination in the same VPN.

51. (Canceled)

- 52. (Currently amended) The system of claim 50 wherein the first header portion is one or the other of an Ethernet header portion or an Internet Protocol (IP) header portion, and the second header portion is one or the other of an Ethernet header portion or an Internet Protocol (IP) header portion.
- 53. (Previously presented) The system of claim 50 wherein the value is derived by performing a hash operation on the first header portion.
- 54. (Previously presented) The system of claim 53 wherein the hash operation is performed on information in the first header portion related to addresses of the source and destination nodes.
- 55. (Previously presented) The system of claim 53 wherein the hash operation is performed on a protocol field in the first header portion.

56. (Canceled)

- 57. (Previously presented) The system of claim 53 wherein the hash operation comprises performing a division on the first header portion.
- 58. (Previously presented) The system of claim 57 wherein the value is related to a remainder generated by the division.
- 59. (Previously presented) The system of claim 53 wherein the hash operation comprises a cyclic redundancy check.
- 60. (Previously presented) The system of claim 53 wherein the hash operation comprises a checksum operation.
- 61. (Previously presented) The system of claim 50 wherein the selecting step comprises performing a hash operation on the second header portion.